



山西瑞杰国际贸易有限公司

GKGD International Trade Co., Ltd

Id: No. 15, west section of Huifeng street, Changzhi economic and Technological Development Zone, Shanxi Provin
Tel: +86 15602330915 Fax: +86 355 5807562 Website: www.gkgd.com

Specification of PM4 Outdoor LED Module

Module		Module photo	
Pixel pitch	4mm		
Pixel Density	62500 dots/m ²		
Pixel configuration	1R1G1B		
LED type	SMD1921		
Module size	W320 *H160mm		
Module weight	435±5g		
Module resolution	W80*H40 dots		
Module QTY/ m ²	19.53 pcs/ m ²		
Min. Viewing Distance	≥4m		
Brightness	≥4500 cd/m ²		
Viewing Angle	H≥160° V≥140°		
Driving Mode	1/10 scan constant current		
Interface	HUB75E		
Input voltage	5VDC		
Max. Power Consumption	33W / Piece		
Avg. Power Consumption	17W / Piece		
Max. Current	6.5 A		
Signal Processing Depth	16384		
Vedio frame rate	60 frames/s		
Refresh Rate	≥1920Hz		
Defective Dots Rate	<0.0001 (LED industry standard: ≤ 0.0003)		
Decay Rate(Operate 3 year)	≤15%		
Brightness Conformity	≥97%		
Colors	281 trillion		
MTBF	≥10000 hours		
Lifespan	≥100000 hours		
Protective function	Over-heat/Over-load /Power-down /Power-leakage /Lightning-protection etc.		
Operating Temperature	-20°C ~ +60°C		
Operating Humidity	10-80% no condensation		
Storage Temperature	-20°C ~ +60°C		
Storage Humidity	10-80% no condensation		
Control system parameter			
Color temperature	Adjustable by software.		
Brightness level	256 levels, automatic or manual adjustment.		
Control way	Computer, real-time, off-line, wireless, internet etc.		
Communication Distance	Cat5 UTP 100 meters, max. 130 meters; or optical fiber.		
Packing			
Carton	40pcs/carton		

Note: The specification may subject to change without prior notice.

